



Normal Series Metal Shaft Slide Potentiometer

A. Shaft Illustration (All in Metal Type)

MATERIAL	SL20V2 SL30V2										
LEVER TYPE	A-TYPE					C-TYPE					
DIMENSIONS											
LENGTH(L)	L	10	15	20	25	12	L	15	20		
	F	7	10	10	10	10	F	10	10		
	M	7	7	7	7	7					

B. Dust-Proof is Available



Normal Series Metal Shaft Slide Potentiometer

Electrical Characteristics

Total Resistance	5KΩ~1MΩ				
Total Resistance Tolerance	± 20%				
Resistance Taper	A. B. C. D. W. Taper				
Resistance Taper Characteristics	A50%	B50%	C50%	D50%	W50%
	15-25%	40-60%	75-85%	2-15%	45-55%
Rated Power	B Taper: AC200V 0.1 W; Other Tapers: AC150V 0.05 W				
Residual Resistance	$R \geq 250K\Omega$ 0.1% $250K\Omega > R > 10K\Omega$ 20Ω Max. (between Term. 1, 2) $10K\Omega \geq R$ 20Ω Max. (between Term. 2, 3)				
Gang Error	-40 ~ 0db ≤ 3db				
Noise	100mV Max.				
Insulation Resistance	DC 500V 50MΩ				
Withstand Voltage	1 minute at AC 300V				
Sliding Life	15,000 Cycles				

Mechanical Characteristics

Overall Travel	20 mm ± 0.5 mm
Stopper Strength	5 kgf.cm max. / 3 sec. (From the base level to a point of 2mm)
Operating Force	20~260gf.cm
Click slip-out force	50gf.cm ~ 350 gf.cm
Lever Push-Pull Strength	5 kgf.cm max. at 10 sec.
Lever Wobble	2(2*L)/25 mm max. (L: lever length both side)
Bending Moment	25mN.m (250gf.cm)
Lever Deviation	0.5 max. (one side)